
Sunbuster End Panel order form for Roll Out Awning

Order date Sales Person	1
Date Req	
Dealers Details	
Address	P/C
Ph Fax	Contact
Customers Name	
Address	P/C
Ph Fax	Mob
RV Brand	
	Awning Brand:
	Sunbuster Colour Required:
	A. Awning fabric length at Roller A.
в	B. Vinyl fabric length from side of van/pop top surround to B.
	roller sailgrove
	C. Back wall height, sailtrack to
Projection = saligrove to side of van parallel to the ground	ground, measured over the C .
Paranet to the ground	wheels/axle
	D. Wall projection, measured
c //	from sidewall to roller sailgrove D .
	Lengual beight epilopous to
Position so the sailgrove is 1850mm	E. Longwall height, sailgrove to ground set at 1850mm. Advise E.
to the ground = E. If not 1850mm PLEASE ADVISE required hightset	
	NB> With the Awning erected to the above measurements
	please ensure that the door of RV is free to open, and there
	is sufficient slope for water to run off. If not adjust as spec
↓ ↓	above, advise the required adjusted height
	AFK brand
NOTES AND OTHER BENEFICIAL INFO:-	AFK track length
	Distance from awning vinyl to front of van body:
Note the valley in	
	e vinyl roof to
1 1 1	atch rainwater.
Refer to ROA	



manufacturers recomendations

Empty groove at 6 o'clock, facing the pavement





www.sunbustershades.com.au admin@sunbustershades.com.au Ph: 1800 472 665

© Copyright Sunbuster Shades ABN 69 137 008 869 ROA Meas Plan 1/1/2021

Mob: 0429 846 628